


Flexus Sauna

Flexible LED for extreme humidity and temperatures



Applications

- Saunas
- Steam Rooms

Features

- 100% Max Ambient Humidity
- 90°C Ambient Working Temperature
- High quality lighting
- Vertical & Horizontal bend
- 50-120-300mm min bend diameters
- IP67 as standard
- Power from one or both ends
- Environmentally friendly
- Energy efficient
- Solvent, Flame and salt resistant
- Silicone material

Technical Information

Type	FX2	FX3	FX6
Bending	Horizontal	Vertical or Horizontal	Vertical
Lumen Output (lm/m)			
White	200	290	450
Red	105	190	150
Green	200	390	350
Blue	40	75	85
Amber	110	190	150
R	50	45	60
G	120	120	210
B	25	20	45
RGB	195	185	315
Cutting (mm)	83	55	166
Min Bend Diameter (mm)	120	300	50
Power (W/m)	6		
CCT	2200K • 2700K • 3000K • 3500K • 4000K 5700K • 6500K • Red • Green • Blue • Amber • RGB		
Material	Silicone		
CRI	80		
Control	Switched • Phase Dimming • DALI • 0-10V		
LED	2835		
Binning	<5 SCDM		
Input Voltage (V)	24		
IP Rating	IP67		
Operating Ambient Temp	90°C Max		
Ambient Relative Humidity	100%		
Max Length (1 Lead)	10m		
Connection	5mtr tail to bare end		

Product Code

SAU-1-2-3-4-5-6

Create your product code by choosing your specification from the product areas.

Final example codes are shown to the right.

Example Codes

SAU-FX2-822-HB-1E-67-XXXX


SAU-FX3-822-HB-1E-67-XXXX

1 Type		2 CCT		3 Bending		4 Cable Entry		5 IP Rating		
Flexus 2	FX2	2200K	822	Vertical**	VB	1 End Feed	1E	IP67	67	
Flexus 3	FX3	2700K	827	Horizontal	HB	1 Side Feed	1S			
Flexus 6	FX6	3000K	830			1 Rear Feed	1R	6 Length		
		3500K	835			2 End Feed	2E			
		4000K	840			2 Side Feed	2S		XXXXmm	XXXX
		5700K	857			2 Rear Feed	2R			
		6500K*	865							
		R	R			* 6500K FX6 only				
		G	G			** FX2 HB Bending only, FX6 VB Bending only				
		B	B							
		Amber	A							
		RGB	RGB							


* 6500K FX6 only

** FX2 HB Bending only, FX6 VB Bending only

Cable Entry Options



⚠ Assembly Caution



SAU-0522

Complies with EN60598-1 and pertinent regulations

Specifications are subject to change without prior notice. Please refer to our website for most up to date version.



Contact our sales team for further assistance











0113 263 9039

sales@kempsonlighting.com

kempsonarchitecturallighting.com

Flexus Sauna

Fixing Accessories

Description	Kemps Code	Specification Drawings	
Serrated Aluminium Profile 2000mm	FX2-SAP-2000	 Flexus 2	 Serrated Aluminium Profile
Serrated Aluminium Profile 1000mm	FX2-SAP-1000		
Serrated Aluminium Profile 500mm	FX2-SAP-0500		
Serrated Aluminium Profile 20mm	FX2-SAP-0020		
Flexible Serrated Aluminium Profile 1000mm	FX2-FSP-1000	 Serrated Recessed Aluminium Profile	 Flexible Serrated Aluminium Profile
Flexible Serrated Aluminium Profile 500mm	FX2-FSP-0500		
Serrated Recessed Aluminium Profile 2000mm	FX2-SRP-2000		
Serrated Recessed Aluminium Profile 1000mm	FX2-SRP-1000		
Serrated Recessed Aluminium Profile 500mm	FX2-SRP-0500	 Flexus 3	 Serrated Aluminium Profile
Serrated Recessed Aluminium Profile 20mm	FX2-SRP-0020		
Serrated Aluminium Profile 2000mm	FX3-SAP-2000		
Serrated Aluminium Profile 1000mm	FX3-SAP-1000		
Serrated Aluminium Profile 500mm	FX3-SAP-0500	 Serrated Recessed Aluminium Profile	 Flexible Serrated Aluminium Profile
Serrated Aluminium Profile 20mm	FX3-SAP-0020		
Flexible Serrated Aluminium Profile 1000mm (HB only)	FX3-FSP-1000		
Flexible Serrated Aluminium Profile 500mm (HB only)	FX3-FSP-0500		
Serrated Recessed Aluminium Profile 2000mm	FX3-SRP-2000	 Flexus 6	 Standard Mounting Aluminium Profile
Serrated Recessed Aluminium Profile 1000mm	FX3-SRP-1000		
Serrated Recessed Aluminium Profile 500mm	FX3-SRP-0500		
Serrated Recessed Aluminium Profile 20mm	FX3-SRP-0020		
Standard Mounting Aluminum Profile 2000mm	FX6-SMP-2000		
Standard Mounting Aluminum Profile 1000mm	FX6-SMP-1000		
Standard Mounting Aluminum Profile 500mm	FX6-SMP-0500		
Standard Mounting Aluminum Profile 35mm	FX6-SMP-0035		

Complies with EN60598-1 and pertinent regulations

Specifications are subject to change without prior notice. Please refer to our website for most up to date version.



Contact our sales team for further assistance

0113 263 9039

sales@kempslighting.com

kempsarchitecturallighting.com