

Flexus 2 Silicone

Dim to Warm Flexible LED



Applications

- Counters
- Decorative
- Facades
- Landscapes
- Pools

Features

- Control of colour temperature and brightness
- 80 CRI
- High quality homogenous light
- Horizontal bend
- 120mm min bend diameter
- Exterior use/under water
- IP68
- Power from one end
- Environmentally friendly
- Energy efficient
- UV resistant
- Silicone material

Technical Information

Lumen Output (lm/m)	340 (3000K)
Power (W/m)	12
Material	Silicone
Bending	Horizontal
CCT	1800K > 3000K
CRI	80
Control	0-10V • DALI • DMX
Beam Angle	115°
LED	Epistar 5050
Binning	3 Step MacAdam
Input Voltage (V)	24
Max length (1 Feed)	15m
Cutting	83mm
IP Rating	IP68
Operating Ambient Temp	-40°C to 55°C
Lifetime	>50,000hrs
Connection	5mtr tail to bare end

Product Code

FX2-S-1-2-3-4-5

Create your product code by choosing your specification from the product areas.

Final example codes are shown to the right.

Example Codes

FX2-S-1830-HB-1E-68-XXXX

FX2-S-1830-HB-1R-68-XXXX

1 CCT

1800K > 3000K **1830**

2 Bend

Horizontal **HB**

3 Cable Entry

1 End Feed **1E**

1 Side Feed **1S**

1 Rear Feed **1R**

2 End Feed **2E**

2 Side Feed **2S**

2 Rear Feed **2R**


4 IP Rating

IP68 *Max 5m depth* **68**

5 Length


TBC **XXXX**

Cable Entry Options



Assembly Caution

Min Bend Dia is **120mm**



FX2-S-DIM-0522

Complies with EN60598-1 and pertinent regulations

Specifications are subject to change without prior notice. Please refer to our website for most up to date version.



Contact our sales team for further assistance

0113 263 9039

sales@kempsonlighting.com

kempsonarchitecturallighting.com

Flexus 2

Fixing Accessories



Description	Kemps Code	Specification Drawings
Serrated Aluminium Profile 2000mm	FX2-SAP-2000	 Flexus 2
Serrated Aluminium Profile 1000mm	FX2-SAP-1000	
Serrated Aluminium Profile 500mm	FX2-SAP-0500	
Serrated Aluminium Profile 20mm	FX2-SAP-0020	
Flexible Serrated Aluminium Profile 1000mm	FX2-FSP-1000	 Serrated Aluminium Profile
Flexible Serrated Aluminium Profile 500mm	FX2-FSP-0500	
Serrated Recessed Aluminium Profile 2000mm	FX2-SRP-2000	 Flexible Serrated Aluminium Profile
Serrated Recessed Aluminium Profile 1000mm	FX2-SRP-1000	
Serrated Recessed Aluminium Profile 500mm	FX2-SRP-0500	
Serrated Recessed Aluminium Profile 20mm	FX2-SRP-0020	
Ceiling Mounting Clip (to be ordered with Serrated Recessed Profile)	FX2-CMC	 Serrated Recessed Aluminium Profile
Transparent Plastic Profile 2000mm	FX2-TPP-2000	
Transparent Plastic Profile 1000mm	FX2-TPP-1000	
Transparent Plastic Profile 500mm	FX2-TPP-0500	
Transparent Plastic Profile 20mm	FX2-TPP-0035	 Transparent Plastic Profile
White Plastic Profile 2000mm	FX2-WPP-2000	
White Plastic Profile 1000mm	FX2-WPP-1000	 S/S Curved Profile
White Plastic Profile 500mm	FX2-WPP-0500	
White Plastic Profile 50mm	FX2-WPP-0050	 Ceiling Mounting Profile (to be supplied with Recessed Mounting Profile)
Flexible Stainless Steel Profile 900mm	FX2-FSSP-0900	
Flexible Stainless Steel Profile 500mm	FX2-FSSP-0500	
Flexible Stainless Steel Profile 300mm	FX2-FSSP-0300	
Flexible Stainless Steel Profile 100mm	FX2-FSSP-0100	


Underwater Applications




Fresh Water



Sea Water
(Salinity<4%)



Swimming Pool
(Chlorine<2PPM)



Swimming Pool
(Ozone<0.3PPM)

Complies with EN60598-1 and pertinent regulations

Specifications are subject to change without prior notice. Please refer to our website for most up to date version.



Contact our sales team for further assistance

0113 263 9039

sales@kempslighting.com

kempsarchitecturallighting.com