

Flexus 2 PVC

Dynamic White Flexible LED



Applications

- Counters
- Decorative
- Facades
- Landscapes

Features

- Colour temperature control
- 2200K up to 5700K
- High quality homogenous light
- Horizontal bend
- 120mm min bend diameter
- Interior or exterior
- IP67 as standard, IP68 available
- Environmentally friendly
- Energy efficient
- Solvent, Flame and salt resistant
- PVC material

Technical Information

Lumen Output (lm/m)	140 > 170
Power (W/m)	12
Material	PVC
Bending	Horizontal
CCT	2200K > 5700K
Control	DALI • DMX • Bluetooth
Beam Angle	120°
LED	Nichia • Epistar
Binning	3 Step MacAdam
Input Voltage (V)	24
Max length (1 Feed)	10mtr
Cutting	83mm
IP Rating	IP67 • IP68
Operating Ambient Temp	-20°C to 45°C
Lifetime	>30,000hrs
Connection	5mtr tail to bare end

Product Code

FX2 - P - 1 - 2 - 3 - 4 - 5

Create your product code by choosing your specification from the product areas.

Final example codes are shown to the right.

Example Codes

FX2-P-2257-HB-1E-67-XXXX

FX2-P-2257-HB-1R-68-XXXX

1 CCT

2200K-5700K **2257**

2 Bend

Horizontal **HB**

3 Cable Entry

1 End Feed	1E
1 Side Feed	1S
1 Rear Feed	1R
2 End Feed	2E
2 Side Feed	2S
2 Rear Feed	2R


4 IP Rating

IP67	67
IP68 <i>Max 2m depth</i>	68

5 Length


XXXXmm **XXXX**

Cable Entry Options



Assembly Caution

Min Bend Dia is **120mm**



FX2-P-0522

Complies with EN60598-1 and pertinent regulations

Specifications are subject to change without prior notice. Please refer to our website for most up to date version.



Contact our sales team for further assistance

0113 263 9039











sales@kempslighting.com

kempsarchitecturallighting.com



Flexus 2

Fixing Accessories

Description	Kemps Code	Specification Drawings
Serrated Aluminium Profile 2000mm	FX2-SAP-2000	   <p>Flexus 2 Serrated Aluminium Profile Flexible Serrated Aluminium Profile</p>
Serrated Aluminium Profile 1000mm	FX2-SAP-1000	
Serrated Aluminium Profile 500mm	FX2-SAP-0500	
Serrated Aluminium Profile 20mm	FX2-SAP-0020	
Flexible Serrated Aluminium Profile 1000mm	FX2-FSP-1000	   <p>Serrated Recessed Aluminium Profile Transparent Plastic Profile S/S Curved Profile</p>
Flexible Serrated Aluminium Profile 500mm	FX2-FSP-0500	
Serrated Recessed Aluminium Profile 2000mm	FX2-SRP-2000	
Serrated Recessed Aluminium Profile 1000mm	FX2-SRP-1000	
Serrated Recessed Aluminium Profile 500mm	FX2-SRP-0500	 <p>Ceiling Mounting Profile (to be supplied with Recessed Mounting Profile)</p>
Serrated Recessed Aluminium Profile 20mm	FX2-SRP-0020	
Ceiling Mounting Clip (to be ordered with Serrated Recessed Profile)	FX2-CMC	
Transparent Plastic Profile 2000mm	FX2-TPP-2000	
Transparent Plastic Profile 1000mm	FX2-TPP-1000	 <p>Ceiling Mounting Profile (to be supplied with Recessed Mounting Profile)</p>
Transparent Plastic Profile 500mm	FX2-TPP-0500	
Transparent Plastic Profile 20mm	FX2-TPP-0035	
White Plastic Profile 2000mm	FX2-WPP-2000	
White Plastic Profile 1000mm	FX2-WPP-1000	 <p>Ceiling Mounting Profile (to be supplied with Recessed Mounting Profile)</p>
White Plastic Profile 500mm	FX2-WPP-0500	
White Plastic Profile 50mm	FX2-WPP-0050	
Flexible Stainless Steel Profile 900mm	FX2-FSSP-0900	
Flexible Stainless Steel Profile 500mm	FX2-FSSP-0500	 <p>Ceiling Mounting Profile (to be supplied with Recessed Mounting Profile)</p>
Flexible Stainless Steel Profile 300mm	FX2-FSSP-0300	
Flexible Stainless Steel Profile 100mm	FX2-FSSP-0100	

Complies with EN60598-1 and pertinent regulations

Specifications are subject to change without prior notice. Please refer to our website for most up to date version.



Contact our sales team for further assistance

0113 263 9039

sales@kempslighting.com

kempsarchitecturallighting.com

