

# Flexus 2 Silicone

Single Colour Flexible LED



5-Year  
Warranty



IP68  
Rating



Flame  
Resistant



Solvent  
Resistant



Saltwater  
Resistant



RoHS  
Compliant



CE  
Certified



UK CA  
Assessed

## Applications

- Counters
- Decorative
- Facades
- Landscapes
- Pools

## Features

- High quality homogenous light
- Horizontal bend
- 80 CRI & 90 CRI
- 120mm min bend diameter
- Exterior use/under water
- IP68
- Power from one or both ends
- Environmentally friendly
- Energy efficient
- UV resistant
- Silicone material

## Technical Information

	White	Red	Green	Blue	Amber
<b>Lumen Output (lm/m)</b>	340	130	350	70	130
<b>Power (W/m)</b>	12	8	12	12	8
<b>Material</b>	Silicone				
<b>Bending</b>	Horizontal				
<b>CCT</b>	Red • Green • Blue • Amber • 2200K • 2700K • 3000K • 3500K • 4000K • 5700K				
<b>CRI</b>	>80 • >90				
<b>Control</b>	Switched • 0-10V • DALI • DMX • Phase • Bluetooth				
<b>Beam Angle</b>	120°				
<b>LED</b>	Nichia • Epistar				
<b>Binning</b>	3 Step MacAdam				
<b>Input Voltage (V)</b>	24				
<b>Max length (1 Feed)</b>	Red • Amber: 20m White • Green • Blue: 15m				
<b>Cutting</b>	Red • Amber: 125mm White • Green • Blue: 83mm				
<b>IP Rating</b>	IP68				
<b>Operating Ambient Temp</b>	-40°C to 55°C				
<b>Lifetime</b>	>50,000hrs				
<b>Connection</b>	5mtr tail to bare end				

## Product Code

### FX2-S-1-2-3-4-5

Create your product code by choosing your specification from the product areas.

Final example codes are shown to the right.

Example Codes

FX2-S-927-HB-1E-68-XXXX

FX2-S-930-HB-2E-68-XXXX

#### 1 CCT

>80CRI - 2200K	<b>822</b>
>80CRI - 2700K	<b>827</b>
>80CRI - 3000K	<b>830</b>
>80CRI - 3500K	<b>835</b>
>80CRI - 4000K	<b>840</b>
>80CRI - 5700K	<b>857</b>
>90CRI - 2700K	<b>927</b>
>90CRI - 3000K	<b>930</b>
>90CRI - 3500K	<b>935</b>
>90CRI - 4000K	<b>940</b>
Red	<b>R</b>
Green	<b>G</b>
Blue	<b>B</b>
Amber	<b>A</b>

#### 2 Bend

Horizontal	<b>HB</b>
------------	-----------

#### 3 Cable Entry

1 End Feed	<b>1E</b>
1 Side Feed	<b>1S</b>
1 Rear Feed	<b>1R</b>
2 End Feed	<b>2E</b>
2 Side Feed	<b>2S</b>
2 Rear Feed	<b>2R</b>

#### 4 IP Rating

IP68 Max 5m depth	<b>68</b>
-------------------	-----------



#### 5 Length

XXXXmm	<b>XXXX</b>
--------	-------------

## Cable Entry Options

## Assembly Caution

Min Bend Dia is **120mm**



FX2-S-0522

Complies with EN60598-1 and pertinent regulations

Specifications are subject to change without prior notice. Please refer to our website for most up to date version.



**Contact our sales team for further assistance**

0113 263 9039

[sales@kempsonlighting.com](mailto:sales@kempsonlighting.com)

[kempsonarchitecturallighting.com](http://kempsonarchitecturallighting.com)

# Flexus 2

## Fixing Accessories



Description	Kemps Code	Specification Drawings
Serrated Aluminium Profile 2000mm	<b>FX2-SAP-2000</b>	<p>Flexus 2</p> <p>Serrated Aluminium Profile</p> <p>Flexible Serrated Aluminium Profile</p>
Serrated Aluminium Profile 1000mm	<b>FX2-SAP-1000</b>	
Serrated Aluminium Profile 500mm	<b>FX2-SAP-0500</b>	
Serrated Aluminium Profile 20mm	<b>FX2-SAP-0020</b>	
Flexible Serrated Aluminium Profile 1000mm	<b>FX2-FSP-1000</b>	<p>Serrated Recessed Aluminium Profile</p> <p>Transparent Plastic Profile</p> <p>S/S Curved Profile</p>
Flexible Serrated Aluminium Profile 500mm	<b>FX2-FSP-0500</b>	
Serrated Recessed Aluminium Profile 2000mm	<b>FX2-SRP-2000</b>	
Serrated Recessed Aluminium Profile 1000mm	<b>FX2-SRP-1000</b>	
Serrated Recessed Aluminium Profile 500mm	<b>FX2-SRP-0500</b>	<p>Ceiling Mounting Profile (to be supplied with Recessed Mounting Profile)</p>
Serrated Recessed Aluminium Profile 20mm	<b>FX2-SRP-0020</b>	
Ceiling Mounting Clip (to be ordered with Serrated Recessed Profile)	<b>FX2-CMC</b>	
Transparent Plastic Profile 2000mm	<b>FX2-TPP-2000</b>	
Transparent Plastic Profile 1000mm	<b>FX2-TPP-1000</b>	
Transparent Plastic Profile 500mm	<b>FX2-TPP-0500</b>	
Transparent Plastic Profile 20mm	<b>FX2-TPP-0035</b>	
White Plastic Profile 2000mm	<b>FX2-WPP-2000</b>	
White Plastic Profile 1000mm	<b>FX2-WPP-1000</b>	
White Plastic Profile 500mm	<b>FX2-WPP-0500</b>	
White Plastic Profile 50mm	<b>FX2-WPP-0050</b>	
Flexible Stainless Steel Profile 900mm	<b>FX2-FSSP-0900</b>	
Flexible Stainless Steel Profile 500mm	<b>FX2-FSSP-0500</b>	
Flexible Stainless Steel Profile 300mm	<b>FX2-FSSP-0300</b>	
Flexible Stainless Steel Profile 100mm	<b>FX2-FSSP-0100</b>	


### Underwater Applications




Fresh Water



Sea Water  
(Salinity<4%)



Swimming Pool  
(Chlorine<2PPM)



Swimming Pool  
(Ozone<0.3PPM)

Complies with EN60598-1 and pertinent regulations

Specifications are subject to change without prior notice. Please refer to our website for most up to date version.



**Contact our sales team for further assistance**

0113 263 9039

[sales@kempslighting.com](mailto:sales@kempslighting.com)

[kempsarchitecturallighting.com](http://kempsarchitecturallighting.com)