

Flexus 3 Silicone

Dynamic White Flexible LED



















CE UK Conformit Certified Assessed

Applications

- Counters
- Decorative
- Facades

- Landscapes
- Pools

Features

- Colour temperature control
- 2200K up to 5700K
- 80 CRI
- High quality homogenous light
- · Vertical & Horizontal bend
- 300mm min bend diameter
- Interior or exterior
- IP68
- Environmentally friendly

- Energy efficient
- UV resistant
- Silicone material

Technical Information

recinical information				
Lumen Output (lm/m)	Vertical 270 • Horizontal 220			
Power (W/m)				
Material	Silicone			
Bending	Vertical • Horizontal			
ССТ	2200K > 5700K • 2500K > 5000K			
CRI	80			
Control	DALI • DMX • Bluetooth			
Beam Angle	116°			
LED	Nichia • Epistar			
Binning	3 Step MacAdam			
Input Voltage (V)	24			
Max length (1 entry)	15m			
Cutting	83mm			
IP Rating	IP68			
Operating Ambient Temp	-40°C to 55°C			
Lifetime	>50,000hrs			
Connection	5mtr tail to bare end			

1 CCT

2200K-5700K

2500K-5000K

Bend

Vertical

Horizontal

FX3-S-DW-11-2-3-4-5

Create your product code by choosing your specification from the product areas.

HB

Final example codes are shown to the right.


	3 Cable Entry	
82257	1 End Feed	1E
82550	1 Side Feed	1S
	1 Rear Feed	1R
	2 End Feed	2E
	2 Side Feed	2S
VB	2 Rear Feed	2R

Example Codes

FX3-S-DW-82257-VB-1E-68-XXXX FX3-S-DW-82550-HB-1R-68-XXXX

4 IP Rating			
IP68 Max 5m depth	68		
5 Length			
XXXXmm	XXXX		


Cable Entry Options





Assembly Caution

Min Bend Dia is 300mm



FX3-S-DW-0522

Complies with EN60598-1 and pertinent regulations

Specifications are subject to change without prior notice. Please refer to our website for most up to date version.



Flexus 3




Fixing Accessories

Description

Kemps Code Specification Drawings


		_	
Serrated Aluminium Profile 2000mm	FX3-SAP-2000		14.9
Serrated Aluminium Profile 1000mm	FX3-SAP-1000	m	20,2
Serrated Aluminium Profile 500mm	FX3-SAP-0500	20,8	500
Serrated Aluminium Profile 20mm	FX3-SAP-0020		
Transparent Plastic Profile 2000mm	FX3-TPP-2000	16.0	20,2
Transparent Plastic Profile 1000mm	FX3-TPP-1000	Flexus 3	Serrated Flexible
Transparent Plastic Profile 500mm	FX3-TPP-0500		S/S Profile
Transparent Plastic Profile 20mm	FX3-TPP-0035		30,0
Serrated Recessed Aluminium Profile 2000mm	FX3-SRP-2000	23,5	8,02
Serrated Recessed Aluminium Profile 1000mm	FX3-SRP-1000	~	
Serrated Recessed Aluminium Profile 500mm	FX3-SRP-0500		
Serrated Recessed Aluminium Profile 20mm	FX3-SRP-0020	20,0	20,2
		Transparent	
Ceiling Mounting Clip (to be ordered with Serrated Recessed Profile)	FX3-CMC	Mounting F	
			20,2
Hybrid Aluminium & Clear Plastic Profile 2000mm	FX3-HBP-2000		
Hybrid Aluminium & Clear Plastic Profile 1000mm	FX3-HBP-1000		
Hybrid Aluminium & Clear Plastic Profile 500mm	FX3-HBP-0500	53.0	
Hybrid Aluminium & Clear Plastic Profile 20mm	FX3-HBP-0035		
Flexible Stainless Steel Profile 900mm	FX3-FSSP-0900	20.8	
Flexible Stainless Steel Profile 500mm	FX3-FSSP-0500	Hybrid Aluminium & Clear Plastic	
Flexible Stainless Steel Profile 300mm	FX3-FSSP-0300	Clear Plastic Profile	Ceiling Mounting Clip (to be supplied with Serrated Recessed Mounting Profile)


Underwater Applications





FX3-FSSP-0100





Fresh Water

Sea Water (Salinity<4%)

Swimming Pool (Chlorine<2PPM)

Swimming Pool (Ozone<0.3PPM)

Complies with EN60598-1 and pertinent regulations

Flexible Stainless Steel Profile 100mm

Specifications are subject to change without prior notice. Please refer to our website for most up to date version.

