

Flexus 3 Silicone

Dim to Warm Flexible LED



Applications

- Counters
- Decorative
- Facades
- Landscapes
- Pools

Features

- Control of colour temperature and brightness
- High quality homogenous light
- Vertical & Horizontal bend
- 300mm min bend diameter
- Exterior use/under water
- IP68
- Power from one end
- Environmentally friendly
- Energy efficient
- UV resistant
- Silicone material

Technical Information

Lumen Output (lm/m)	600 (3000k)
Power (W/m)	12
Material	Silicone
Bending	Vertical • Horizontal
CCT	1800K > 3000K
Control	0-10V • DALI • DMX •
Beam Angle	115°
LED	Epistar 5050
Binning	3 Step MacAdam
Input Voltage (V)	24
Max length (1 entry)	15m
Cutting	71mm
IP Rating	IP68
Operating Ambient Temp	-40°C to 55°C
Lifetime	>50,000hrs
Connection	5mtr tail to bare end

Product Code

FX3-S-1-2-3-4-5

Create your product code by choosing your specification from the product areas.

Final example codes are shown to the right.


Example Codes

FX3-S-1830-HB-1E-68-XXXX

FX3-S-1830-VB-1S-68-XXXX


1 CCT	2 Bend	3 Cable Entry	4 IP Rating	5 Length
1800k>3000k 1830	Vertical VB Horizontal HB	1 End Feed 1E 1 Side Feed 1S 1 Rear Feed 1R 2 End Feed 2E 2 Side Feed 2S 2 Rear Feed 2R	IP68 <i>Max 5m depth</i> 68	5 Length XXXXmm XXXX

Cable Entry Options



Assembly Caution

Min Bend Dia is **300mm**



FX3-S-DIM-0522

Complies with EN60598-1 and pertinent regulations

Specifications are subject to change without prior notice. Please refer to our website for most up to date version.



Contact our sales team for further assistance







0113 263 9039

sales@kempsonlighting.com

kempsonarchitecturallighting.com

Flexus 3

Fixing Accessories

Description	Kemps Code	Specification Drawings
Serrated Aluminium Profile 2000mm	FX3-SAP-2000	 <p>Flexus 3 Serrated Aluminium Profile Flexible S/S Profile</p>
Serrated Aluminium Profile 1000mm	FX3-SAP-1000	
Serrated Aluminium Profile 500mm	FX3-SAP-0500	
Serrated Aluminium Profile 20mm	FX3-SAP-0020	
Transparent Plastic Profile 2000mm	FX3-TPP-2000	 <p>Transparent Plastic Mounting Profile Serrated Recessed Aluminium Profile</p>
Transparent Plastic Profile 1000mm	FX3-TPP-1000	
Transparent Plastic Profile 500mm	FX3-TPP-0500	
Transparent Plastic Profile 20mm	FX3-TPP-0035	
Serrated Recessed Aluminium Profile 2000mm	FX3-SRP-2000	 <p>Hybrid Aluminium & Clear Plastic Profile</p>
Serrated Recessed Aluminium Profile 1000mm	FX3-SRP-1000	
Serrated Recessed Aluminium Profile 500mm	FX3-SRP-0500	
Serrated Recessed Aluminium Profile 20mm	FX3-SRP-0020	
Ceiling Mounting Clip (to be ordered with Serrated Recessed Profile)	FX3-CMC	 <p>Ceiling Mounting Clip (to be supplied with Serrated Recessed Mounting Profile)</p>
Hybrid Aluminium & Clear Plastic Profile 2000mm	FX3-HBP-2000	 <p>Flexible Stainless Steel Profile</p>
Hybrid Aluminium & Clear Plastic Profile 1000mm	FX3-HBP-1000	
Hybrid Aluminium & Clear Plastic Profile 500mm	FX3-HBP-0500	
Hybrid Aluminium & Clear Plastic Profile 20mm	FX3-HBP-0035	
Flexible Stainless Steel Profile 900mm	FX3-FSSP-0900	 <p>Flexible Stainless Steel Profile</p>
Flexible Stainless Steel Profile 500mm	FX3-FSSP-0500	
Flexible Stainless Steel Profile 300mm	FX3-FSSP-0300	
Flexible Stainless Steel Profile 100mm	FX3-FSSP-0100	


Underwater Applications




Fresh Water



Sea Water
(Salinity<4%)



Swimming Pool
(Chlorine<2PPM)



Swimming Pool
(Ozone<0.3PPM)

Complies with EN60598-1 and pertinent regulations

Specifications are subject to change without prior notice. Please refer to our website for most up to date version.



Contact our sales team for further assistance

0113 263 9039

sales@kempslighting.com

kempsarchitecturallighting.com