

Flexus 3 Silicone

RGBW Colour Changing Flexible LED



5-Year
Warranty



IP68
Rating



UV
Resistant



Flame
Resistant



Solvent
Resistant



Saltwater
Resistant



RoHS
Compliant



CE
Certified



UK CA
Assessed

Applications

- Counters
- Decorative
- Facades
- Landscapes
- Pools

Features

- Colour changing effects
- High quality homogenous light
- Vertical & Horizontal bend
- 300mm min bend diameter
- Interior or exterior
- IP68
- Environmentally friendly
- Energy efficient
- UV resistant
- Silicone material

Technical Information

Lumen Output (lm/m)	Red 85 • Green 220 • Blue 35 • White 220
Power (W/m)	15
Material	Silicone
Bending	Vertical • Horizontal
CCT	RGBW 2700K • RGBW 3000K • RGBW 4000K
Control	DALI • DMX • Casambi
Beam Angle	113°
LED	Nichia • Epistar
Binning	3 Step MacAdam
Input Voltage (V)	24
Max length (1 entry)	8m
Cutting	83mm
IP Rating	IP68
Operating Ambient Temp	-40°C to 55°C
Lifetime	>50,000hrs
Connection	5mtr tail to bare end

Product Code

FX3-S-1-2-3-4-5

Create your product code by choosing your specification from the product areas.

Final example codes are shown to the right.

Example Codes

FX3-S-RGBW27-HB-1E-68-XXXX



FX3-S-RGBW30-VB-1S-68-XXXX

1 CCT		2 Bend		3 Cable Entry		4 IP Rating		
RGBW 2700K	RGBW27	Vertical	VB	1 End Feed	1E	IP68 <i>Max 5m depth</i>	68	
RGBW 3000K	RGBW30	Horizontal	HB	1 Side Feed	1S			
RGBW 4000K	RGBW40			1 Rear Feed	1R	5 Length		
				2 End Feed	2E			
				2 Side Feed	2S		XXXXmm	XXXX
				2 Rear Feed	2R			

Cable Entry Options

Assembly Caution

Min Bend Dia is **300mm**



FX3-S-RGBW-0722

Complies with EN60598-1 and pertinent regulations

Specifications are subject to change without prior notice. Please refer to our website for most up to date version.



Contact our sales team for further assistance






0113 263 9039

sales@kempslighting.com

kempsassitecturallighting.com

Flexus 3

Fixing Accessories

Description	Kemps Code	Specification Drawings
Serrated Aluminium Profile 2000mm	FX3-SAP-2000	 <p>Flexus 3 Serrated Aluminium Profile Flexible S/S Profile</p>
Serrated Aluminium Profile 1000mm	FX3-SAP-1000	
Serrated Aluminium Profile 500mm	FX3-SAP-0500	
Serrated Aluminium Profile 20mm	FX3-SAP-0020	
Transparent Plastic Profile 2000mm	FX3-TPP-2000	 <p>Transparent Plastic Mounting Profile Serrated Recessed Aluminium Profile</p>
Transparent Plastic Profile 1000mm	FX3-TPP-1000	
Transparent Plastic Profile 500mm	FX3-TPP-0500	
Transparent Plastic Profile 20mm	FX3-TPP-0035	
Serrated Recessed Aluminium Profile 2000mm	FX3-SRP-2000	 <p>Hybrid Aluminium & Clear Plastic Profile</p>
Serrated Recessed Aluminium Profile 1000mm	FX3-SRP-1000	
Serrated Recessed Aluminium Profile 500mm	FX3-SRP-0500	
Serrated Recessed Aluminium Profile 20mm	FX3-SRP-0020	
Ceiling Mounting Clip (to be ordered with Serrated Recessed Profile)	FX3-CMC	 <p>Ceiling Mounting Clip (to be supplied with Serrated Recessed Mounting Profile)</p>
Hybrid Aluminium & Clear Plastic Profile 2000mm	FX3-HBP-2000	
Hybrid Aluminium & Clear Plastic Profile 1000mm	FX3-HBP-1000	
Hybrid Aluminium & Clear Plastic Profile 500mm	FX3-HBP-0500	
Hybrid Aluminium & Clear Plastic Profile 20mm	FX3-HBP-0035	
Flexible Stainless Steel Profile 900mm	FX3-FSSP-0900	 <p>Ceiling Mounting Clip (to be supplied with Serrated Recessed Mounting Profile)</p>
Flexible Stainless Steel Profile 500mm	FX3-FSSP-0500	
Flexible Stainless Steel Profile 300mm	FX3-FSSP-0300	
Flexible Stainless Steel Profile 100mm	FX3-FSSP-0100	


Underwater Applications




Fresh Water



Sea Water
(Salinity<4%)



Swimming Pool
(Chlorine<2PPM)



Swimming Pool
(Ozone<0.3PPM)

Complies with EN60598-1 and pertinent regulations

Specifications are subject to change without prior notice. Please refer to our website for most up to date version.



Contact our sales team for further assistance

0113 263 9039

sales@kempslighting.com

kempsarchitecturallighting.com