

Flexus 4 PVC

Single Colour Flexible LED



Applications

- Counters
- Decorative
- Facades
- Landscapes

Features

- High quality homogenous light
- 80CRI & 90CRI
- Vertical & Horizontal bend
- 100mm min bend diameter
- Interior or exterior
- IP65
- Power from one or both ends
- Environmentally friendly
- Energy efficient
- Solvent, Flame and salt resistant
- PVC material

Technical Information

	White	Red	Green	Blue	Amber
Lumen Output (lm/m)	140	50	200	30	50
Power (W/m)	4.5	4.5	4.5	4.5	4.5
Material	PVC				
Bending	Vertical • Horizontal				
CCT	Red • Green • Blue • Amber • 2200K • 2700K • 3000K • 3500K • 4000K • 5700K				
CRI	80 • 90				
Control	Switched • 0-10V • DALI • DMX • Phase • Bluetooth				
Beam Angle	110°				
LED	Nichia • Epistar				
Binning	3 Step MacAdam				
Input Voltage (V)	24				
Max length (1 entry)	10m				
Cutting	83mm				
IP Rating	IP65				
Operating Ambient Temp	-20°C to 45°C				
Lifetime	>30,000hrs				
Connection	5mtr tail to bare end				

Product Code

FX4-P-1-2-3-4-5

Create your product code by choosing your specification from the product areas.

Final example codes are shown to the right.

Example Codes

FX4-P-827-VB-1E-65-XXXX

FX4-P-857-HB-1R-65-XXXX

1 CCT

2700K 90CRI	927	Red	R
3000K 90CRI	930	Green	G
3500K 90CRI	935	Blue	B
4000K 90CRI	940	Amber	A
2200K 80CRI	822		
2700K 80CRI	827		
3000K 80CRI	830		
3500K 80CRI	835	Vertical	VB
4000K 80CRI	840	Horizontal	HB
5700K 80CRI	857		

2 Bend

3 Cable Entry

1 End Feed	1E
1 Side Feed	1S
1 Rear Feed	1R
2 End Feed	2E
2 Side Feed	2S
2 Rear Feed	2R

4 IP Rating

IP65	65
------	----



5 Length

XXXXmm	XXXX
--------	------

Cable Entry Options

Assembly Caution

Min Bend Dia is 100mm



FX4-P-0522

Complies with EN60598-1 and pertinent regulations

Specifications are subject to change without prior notice. Please refer to our website for most up to date version.



Contact our sales team for further assistance

0113 263 9039

sales@kempsonlighting.com

kempsonarchitecturallighting.com




Flexus 4

Fixing Accessories

Description	Kemps Code
Serrated Aluminium Profile 2000mm	FX4-SAP-2000
Serrated Aluminium Profile 1000mm	FX4-SAP-1000
Serrated Aluminium Profile 500mm	FX4-SAP-0500
Serrated Aluminium Profile 20mm	FX4-SAP-0020
Serrated Recessed Aluminium Profile 2000mm	FX4-SRP-2000
Serrated Recessed Aluminium Profile 1000mm	FX4-SRP-1000
Serrated Recessed Aluminium Profile 500mm	FX4-SRP-0500
Serrated Recessed Aluminium Profile 20mm	FX4-SRP-0020
Standard Mounting Aluminium Profile 2000mm	FX4-SMP-2000
Standard Mounting Aluminium Profile 1000mm	FX4-SMP-1000
Standard Mounting Aluminium Profile 500mm	FX4-SMP-0500
Standard Mounting Aluminium Profile 35mm	FX4-SMP-0035
Flexible Serrated Aluminium Profile (HB only) 1000mm	FX4-FSP-1000
Flexible Serrated Aluminium Profile (HB only) 500mm	FX4-FSP-0500
Hybrid Aluminium & Clear Plastic Profile 2000mm	FX4-HBP-2000
Hybrid Aluminium & Clear Plastic Profile 1000mm	FX4-HBP-1000
Hybrid Aluminium & Clear Plastic Profile 500mm	FX4-HBP-0500
Hybrid Aluminium & Clear Plastic Profile 35mm	FX4-HBP-0035

Specification Drawings



Complies with EN60598-1 and pertinent regulations

Specifications are subject to change without prior notice. Please refer to our website for most up to date version.



Contact our sales team for further assistance

0113 263 9039

sales@kempslighting.com

kempsarchitecturallighting.com

