

# Flexus 4 Silicone

Single Colour High Output Flexible LED



## Applications

- Counters
- Facades
- Decorative
- Landscapes

## Features

- High quality homogenous light
- Energy efficient
- Vertical & Horizontal bend
- Solvent, flame and salt resistant
- 100mm min bend diameter
- Silicone material
- Interior or exterior
- IP67
- Power from one or both ends
- Environmentally friendly

## Technical Information

|                        |   |
|------------------------|---|
| Lumen Output (lm/m)    | 420   |
| Power (W/m)            | 9   |
| Material               | Silicone  |
| Bending                | Vertical • Horizontal                             |
| CCT                    | 2200K • 2700K • 3000K • 3500K • 4000K • 5700K     |
| CRI                    | 80  |
| Control                | Switched • 0-10V • DALI • DMX • Phase • Bluetooth |
| Beam Angle             | 110°  |
| LED                    | Nichia • Epistar                                  |
| Binning                | 3 Step MacAdam                                    |
| Input Voltage (V)      | 24  |
| Max length (1 entry)   | 7.5m  |
| Cutting                | 83mm  |
| IP Rating              | IP67  |
| Operating Ambient Temp | -40°C to 45°C                                     |
| Lifetime               | >50,000hrs  |
| Connection             | 5mtr tail to bare end                             |

# Product Code

## FX4-HO-S-1-2-3-4-5

Create your product code by choosing your specification from the product areas.

Final example codes are shown to the right.

Example Codes

FX4-HO-S-827-VB-1E-67-XXXX

FX4-HO-S-857-HB-1R-67-XXXX

| 1 CCT |     | 2 Bend     |    | 3 Cable Entry |    | 4 IP Rating |    |
|-------|-----|------------|----|---------------|----|-------------|----|
| 2200K | 822 | Vertical   | VB | 1 End Feed    | 1E | IP67        | 67 |
| 2700K | 827 | Horizontal | HB | 1 Side Feed   | 1S |             |    |
| 3000K | 830 |            |    | 1 Rear Feed   | 1R |             |    |
| 3500K | 835 |            |    | 2 End Feed    | 2E |             |    |
| 4000K | 840 |            |    | 2 Side Feed   | 2S |             |    |
| 5700K | 857 |            |    | 2 Rear Feed   | 2R |             |    |


  

| 5 Length |      |
|----------|------|
| XXXXmm   | XXXX |

## Cable Entry Options

## ⚠ Assembly Caution

Min Bend Dia is 100mm



FX4-HO-S-0622

Complies with EN60598-1 and pertinent regulations

Specifications are subject to change without prior notice. Please refer to our website for most up to date version.



Contact our sales team for further assistance

0113 263 9039

sales@kempsonlighting.com


kempsonarchitecturallighting.com

# Flexus 4

## Fixing Accessories

| Description  | Kemps Code          |
|--|---------------------|
| Serrated Aluminium Profile 2000mm                    | <b>FX4-SAP-2000</b> |
| Serrated Aluminium Profile 1000mm                    | <b>FX4-SAP-1000</b> |
| Serrated Aluminium Profile 500mm                     | <b>FX4-SAP-0500</b> |
| Serrated Aluminium Profile 20mm                      | <b>FX4-SAP-0020</b> |
| Serrated Recessed Aluminium Profile 2000mm           | <b>FX4-SRP-2000</b> |
| Serrated Recessed Aluminium Profile 1000mm           | <b>FX4-SRP-1000</b> |
| Serrated Recessed Aluminium Profile 500mm            | <b>FX4-SRP-0500</b> |
| Serrated Recessed Aluminium Profile 20mm             | <b>FX4-SRP-0020</b> |
| Standard Mounting Aluminium Profile 2000mm           | <b>FX4-SMP-2000</b> |
| Standard Mounting Aluminium Profile 1000mm           | <b>FX4-SMP-1000</b> |
| Standard Mounting Aluminium Profile 500mm            | <b>FX4-SMP-0500</b> |
| Standard Mounting Aluminium Profile 35mm             | <b>FX4-SMP-0035</b> |
| Flexible Serrated Aluminium Profile (HB only) 1000mm | <b>FX4-FSP-1000</b> |
| Flexible Serrated Aluminium Profile (HB only) 500mm  | <b>FX4-FSP-0500</b> |
| Hybrid Aluminium & Clear Plastic Profile 2000mm      | <b>FX4-HBP-2000</b> |
| Hybrid Aluminium & Clear Plastic Profile 1000mm      | <b>FX4-HBP-1000</b> |
| Hybrid Aluminium & Clear Plastic Profile 500mm       | <b>FX4-HBP-0500</b> |
| Hybrid Aluminium & Clear Plastic Profile 35mm        | <b>FX4-HBP-0035</b> |

## Specification Drawings



Complies with EN60598-1 and pertinent regulations

Specifications are subject to change without prior notice. Please refer to our website for most up to date version.



**Contact our sales team for further assistance**

0113 263 9039

[sales@kempslighting.com](mailto:sales@kempslighting.com)

[kemp architectural lighting.com](http://kemp architectural lighting.com)