


Proteus 4040 P

Pendant Suspended Luminaire



Features

- LED suspended luminaire, direct light distribution.
- CCT options of 2700K, 3000K & 4000K, others available on request.
- Latest Nichia LED technology with CRI80 & 90 available.
- Sleek design, lightweight 38mm x 38mm aluminium body with frosted or microprismatic diffuser options.
- Choice of black, white and grey finish as standard with many custom RAL colours available.
- Various lengths from 500mm > 3000mm.
- Remote Gear - within 10mtrs using 1.5mm cable.

Applications

- Retail
- Hospitality
- Educational
- Commercial
- Public Realm
- Residential

Technical Information

	Low	Medium	High
Power (W/m)	9.6	15	19.2
Lumen Output (lm/m)			
Frosted Diffuser	958	1053	1740
Prismatic Diffuser	1598	1755	2900
Efficacy (lm/W) 4000K Frosted	101	70	92
Efficacy (lm/W) 4000K Prismatic	168	117	153
Input (V)	24		
CCT	2700K • 3000K • 4000K		
CRI	>80 • >90		
LED Chip	Nichia		
Binning	3 Step MacAdam Elipse		
Control	Switched • 0-10V • DALI • DMX • Bluetooth (Casambi)		
Beam Angle	120°		
Lifetime (LM80)	50,000hrs @25°C		
Operating Temp	-25°C to 50°C		
IP Rating	IP40		
Diffuser	Frosted • Microprismatic		
Body Colour	Black • White • Grey • Custom RAL on request.		
Lengths	500mm > 3000mm		

Product Code

PRO4040 - P - 1 - 2 - 3 - 4 - 5 - 6

Example Codes

Create your product code by choosing your specification from the product areas.

PRO4040-P-19.2-830-D-F-9005-XXXX

Final example codes are shown to the right.

PRO4040-P-15-930-B-P-9003-XXXX


1 Power		2 CCT		3 Control			
19.2W	19.2	80CRI - 2700K	827	90CRI - 2700K	927	Switched	S
15W	15	80CRI - 3000K	830	90CRI - 3000K	930	DALI	D
9.6W	9.6	80CRI - 4000K	840	90CRI - 4000K	940	0-10V	O
						Bluetooth Casambi	B
						DMX	X

4 Diffuser		5 Finish		6 Length		Extras - On Request**	
Frosted	F	Jet Black	9005	XXXXmm*	XXXX	Emergency Module	
Prismatic	P	Signal White	9003			Motion Sensors	
		White Aluminium	9006				
		Custom RAL	RAL#				

*Custom lengths, infills and continuous lines available.

**Please enquire with your requirements.

Technical Drawings



Additional Accessories

3D printed ceiling rose 125mm dia (RAL colour on request) - **CR001**

PRO4040-1122

Complies with EN60598-1 and pertinent regulations

Specifications are subject to change without prior notice. Please refer to our website for most up to date version.



Contact our sales team for further assistance

0113 263 9039

sales@kempslighting.com

kempslighting.com

