


Proteus FX

Bendable Linear LED



Applications

- Walls
- Ceilings
- Corridors

Benefits

- Vertical & horizontal bending
- Various colour temperatures available
- Homogenous appearance
- Multiple lengths available to suit
- Dimmable
- Remote gear
- Various lumen outputs
- Curved or circular

Features

- Plaster in luminaire
- Curved to suit ceilings and walls
- 2700K - 3000K - 4000K
- 14.4W - 9.6W
- 80 & 90 CRI
- IP54
- Switched - 0-10V - DALI - Phase - DMX - Bluetooth Casambi
- 5yr warranty

Technical Information

Power (W/m)	4.8W	9.6W	14.4W
Lumen Output (lm/m based on 4000K)	385	700	1472
Input (V)	24		
CCT	2700K • 3000K • 4000K		
CRI	>80 • >90		
Binning	3 Step MacAdam Elipse		
Control	Switched • 0-10V • DALI • Phase • DMX • Bluetooth Casambi		
Beam angle	120°		
Lifetime (LM80)	50,000hrs @25°C		
Operating Temp	-25°C to 55°C		
IP Rating	IP54		
Diffuser	Opal		
Finish	Black • Signal White • Grey • Anodised Aluminium • Custom RAL		
Mounting	Recessed		
Multiple lengths available	50mm increments		

Product Code

PRO - FX - 1 - 2 - 3 - 4 - 5 - 6

Create your product code by choosing your specification from the product areas.

Final example codes are shown to the right.

Example Codes

PRO-FX-14.4-827-O-54-9005-XXXX

PRO-FX-9.6-940-O-54-9003-XXXX

1 Power

14.4W	14.4
9.6W	9.6
4.8W	4.8

2 CCT

	>80CRI	>90CRI
2700K	827	927
3000K	830	930
4000K	840	940

3 Diffuser

Opal	O
------	---

4 IP Rating

IP54	54
------	----




5 Finish

Jet Black	9005
Signal White	9003
Grey	9006
Anodised Aluminium	AA
Custom	RAL#

6 Length

XXXXmm	XXXX
--------	------

Specification Drawings



Each fitting to be supplied with a 1 mtr tail to bare end (24V)

PRO-FX-0122

Complies with EN60598-1 and pertinent regulations

Specifications are subject to change without prior notice. Please refer to our website for most up to date version.



Contact our sales team for further assistance

0113 263 9039

sales@kempslighting.com

kempslighting.com