

Mersus 2

Pixel Inground Linear LED

















Applications

- Landscapes
- Walkways

Decorative

Features

- Individual LED colour control
- Programme endless chasing colour scenes
- Scenes set to your requirements
- In-house programming service
- Technical support provided through to install
- Pre-assembled control equipment for easy install

- Curved or Straight **Applications**
- Endless shapes possible
- 2200K 4500K, Red, Green, Blue, Amber, RGBW, RGB, 2200K-4500K
- IP67
- Silicone Diffuser
- Easy to Install & Maintain
- 3 years warranty

Technical Information

Shape	Straight or Curved			
сст	Red • Green • Blue • Amber • RGBW • RGB • 2200K • 2700K • 3200K • 4500K • 2200K-4500K			
CRI	>80			
Input Voltage (V)	24			
Power (W/m)	Red, Green, Blue, Amber, White, RGB = 24 RGBW = 30 DW = 20			
Control	SPI			
Cut Increments	125mm • 100mm for Dynamic White			
Operating Temp	-20°C to 55°C			
IP Rating	IP67			
IK Rating	IK10			
Minimum Bend Radius (Curved)	750mm			

MER2-PIX-11-2-3

Create your product code by choosing your specification from the product areas.

Final example codes are shown to the right.


Example Codes


MER2-PIX-822-S-1E MER2-PIX-R-SC-1S

1 Colour				2 Shape		3 Cable Entry	
Red	R	2200K	822	Straight	s	1 End Feed	1E
Green	G	2700K	827	Curved	С	1 Side Feed	1S
Blue	В	3200K	832	Straight & Curved	SC		
Amber	Α	4500K	845				
RGBW	RGBW	2200K/4500K	22/45				
RGBW	RGB						

Mersus 2 is manufactured to bespoke shapes and lengths. Please contact our sales team to discuss you requirements.

Specification Drawings





MER2-PIX-0122

Complies with EN60598-1 and pertinent regulations

Specifications are subject to change without prior notice. Please refer to our website for most up to date version.

