

Flexus 360 Silicone

Decorative Flexible LED















ROHS CE UK Conformity Compliant Certified Assessed

Applications

Decorative

Features

- Bendable in all directions
- High quality LED with homogenous appearance
- 100mm min bend radius
- Interior or exterior
- IP65
- Power from one end

- Environmentally friendly
- Energy efficient
- **UV** resistant
- Silicone material

Technical Information

Lumen Output (lm/m)	1152 (4000K)	
Power (W/m)	12	
Material	Silicone	
Bending	All directions	
ССТ	2700K • 3000K • 4000K • 6500K	
CRI	>90	
Control	Switched • 0-10V • DALI • DMX • Phase • Bluetooth	
Beam Angle	360°	
Binning	3 Step MacAdam	
Input Voltage (V)	24	
Max length	5m	
Diameter	18mm	
IP Rating	IP65	
Operating Ambient Temp	-40°C to 45°C	
Lifetime	>50K hrs Internal • >36K External	
Connection	Injection molded 5mtr tail to bare end	

Product Code

FX360-1-2-3-4-5

Create your product code by choosing your specification from the product areas.

Final example codes are shown to the right.

LXai	Tiple	Coues	

FX360-927-12-S-65-XXXX FX360-965-12-P-65-XXXX

XXXX


1 сст	
2700K 90CRI	927
3000K 90CRI	930
4000K 90CRI	940
6500K 90CRI	965

2 Power	
12W	12
_	

3 Mounting


Surface

Suspended



XXXXmm


Specification Drawings



Section

S

Р



Fixing Accessories

Description




Assembly Caution

Flexus 360 Mounting Surface Clips (2 per pack)
Flexus 360 Mounting Ceiling Clips (2 per pack)
Flexus 360 Suspension kit - max length of 1200mm

FX360-005 FX360-006 FX360-007

Kemps Code

Min Bend Dia is 100mm



Complies with EN60598-1 and pertinent regulations

Specifications are subject to change without prior notice. Please refer to our website for most up to date version.

