


Proteus BXL - RGBW

RGBW Colour Changing Linear LED



Applications

- Furniture
- Decorative
- Handrail

Benefits

- Clear or Opal diffuser options
- Internal applications
- Multiple lengths from 122mm - 3022mm
- Maintainable

Features

- RGBW
- 100mm cut increments
- 19.2W per mtr
- DALI - DMX - Bluetooth
- 80 CRI
- 5yr Warranty
- 120° Beam angle
- Re-use luminaire
- IP54 - IP67

Technical Information

Power (W/m)	19.2 (all 4 colours @100%)
Lumen Output (lm/m)	Red 78 • Green 226 • Blue 48 • White 882
Input	24V
Colour	RGBW
CRI	80
LED Chip	Luxeon
Binning	3 Step MacAdam Ellipse
Control	DALI • DMX • Bluetooth
Beam angle	120°
Lifetime (LM80)	50,000hrs @25°C
Operating Temp	-25°C to 55°C
IP Rating	IP54 • IP67
Diffuser	Opal • Clear
Mounting	Fixed • Spring
Multiple lengths available	122mm - 3022mm

Product Code

PRO - BXL - RGBW - 1 - 2 - 3 - 4 - 5 - 6

Create your product code by choosing your specification from the product areas.

Final example codes are shown below.

Example Codes

PRO-BXL-RGBW-19.2-C-67-F-R-XXXX

PRO-BXL-RGBW-19.2-O-54-F-F-XXXX

1 Power

19.2W	19.2
-------	------

2 Diffuser

Clear 120°	C
Opal	O

3 IP Rating

IP54	54
IP67	67

4 Mounting

Fixed	F
Spring	S


5 End Cap

Flat	F
Round	R

6 Length

XXXXmm	XXXX
--------	------

Specification Drawings



Fittings are provided with end cable entry as standard. Extension cable with female socket connector can be purchased separately with the below product code(s).

5 core M12 Female extension lead 10000mm - **CA043**

PRO-BXL-RGBW-0822

Complies with EN60598-1 and pertinent regulations

Specifications are subject to change without prior notice. Please refer to our website for most up to date version.



Contact our sales team for further assistance

0113 263 9039

sales@kempslighting.com

kempslighting.com