


Proteus I - RGBW

RGBW Colour Changing Linear LED



Applications

- General lighting
- Decorative
- Cove

Benefits

- Clear or Opal diffuser options
- Internal or external applications
- Multiple lengths from 124mm - 3024mm
- Maintainable

Features

- RGBW
- 19.2W/m
- 80 CRI
- 120° Beam angle
- IP54 & IP67
- 100mm cut increments
- DALI - DMX - Bluetooth
- 5yr Warranty
- Re-use luminaire

Technical Information

Power (W/m)	19.2 (all 4 colours @100%)
Lumen Output (lm/m)	Red 78 • Green 226 • Blue 48 • White 882
Input	24V
Colour	RGBW
CRI	80
LED Chip	Luxeon
Binning	3 Step MacAdam Elipse
Control	DALI • DMX • Bluetooth
Beam angle	120°
Lifetime (LM80)	50,000hrs @25°C
Operating Temp	-25°C to 55°C
IP Rating	IP54 • IP67
Diffuser	Opal • Clear
Finish	Jet Black • Signal White • Anodised Aluminium • Custom
Mounting	Fixed or Suspended
Multiple lengths available	124mm - 3024mm

Product Code

PRO - I - RGBW - 1 - 2 - 3 - 4 - 5 - 6 - 7

Create your product code by choosing your specification from the product areas.

Final example codes are shown below.


1 Diffuser		3 Brackets		5 Power		7 Length	
Clear 120°	C	Fixed	F	19.2W	19.2	XXXXmm	XXXX
Opal	O	Suspended	S				
2 IP Rating		4 Cable Entry		6 Finish			
IP54	54	End Feed	1E	Jet Black	9005		
IP67	67	Rear Feed	1R	Signal White	9003		
				Anodised Aluminium	9006		
				Custom	RAL#		

Example Codes

PRO-I-RGBW-C-54-F-1E-19.2-9005-XXXX

PRO-I-RGBW-O-67-S-1R-19.2-9003-XXXX

Specification Drawings



Fittings are provided with end cable entry as standard. Extension cable with female socket connector can be purchased separately with the below product code(s).

5 core M12 Female extension lead 10000mm - **CA043**

PRO-I-RGBW-0822

Complies with EN60598-1 and pertinent regulations

Specifications are subject to change without prior notice. Please refer to our website for most up to date version.



Contact our sales team for further assistance

0113 263 9039

sales@kempslighting.com

kempslighting.com