

# **Proteus R - RGBW**

















**RGBW Colour Changing Linear LED** 

# **Applications**

**Furniture** 

Decorative

Handrail

Cove

## **Benefits**

- Clear or Opal diffuser options •
- Multiple lengths from 125mm
  - 2925mm

- Internal applications
- Maintainable

#### **Features**

- **RGBW**
- 19.2W per mtr
- 80 CRI
- 120° or 12° Beam angle
- IP54 IP67

- 100mm cut increments
- DALI DMX Bluetooth
- **5yr Warranty**
- Re-use luminaire

## **Technical Information**

D /\A//\	<b>D</b> (W) (10.0 ( W) (10.00)				
Power (W/m)	19.2 (all 4 colours @100%)				
Lumen Output (Im/m)	Red 78 • Green 226 •				
	Blue 48 • White 882				
Input	24V				
Colour	RGBW (3000K)				
CRI	80				
LED Chip	Nichia				
Binning	3 Step MacAdam Elipse				
Control	DALI • DMX • Bluetooth				
Beam angle	120° • 12°				
Lifetime (LM80)	50,000hrs @25°C				
Operating Temp	-25°C to 55°C				
IP Rating	IP54 • IP67				
Diffuser	Opal • Clear				
Mounting	Fixed • Adjustable				
Multiple lengths available	125mm - 2925mm				

### **Product Code**

## PRO-R-RGBW-11-2-3-4-5

Create your product code by choosing your specification from the product areas.

Final example codes are shown below.


Example Codes


PRO-R-RGBW-19.2-C-54-F-XXXX PRO-R-RGBW-19.2-O-67-A-XXXX

1 Power		3 IP Rating	
19.2W	19.2	IP54 IP67	54 67
2 Diffuser		4 Mounting	
Clear 120°	С	Fixed	F
Opal	0	Adjustable	Α
Clear 12°	C1		
		6 Length	

XXXXmm

# **Specification Drawings**





Fittings are provided with end cable entry as standard. Extension cable with female socket connector can be purchased separately with the below product code(s).

5 core M12 Female extension lead 10000mm - CA043

PRO-R-RGBW-0822

XXXX

Complies with EN60598-1 and pertinent regulations

Specifications are subject to change without prior notice. Please refer to our website for most up to date version.

