



Flexus 8

Colour Changing Flexible Wall Grazer



Applications

- Curved walls and features
- Columns
- Wall Grazing
- Facades

Features

- Vertical & horizontal combined bending
- High quality LED
- 400mm or 800mm min bend diameters
- Interior or exterior
- IP67
- Power from one end
- Environmentally friendly
- Energy efficient
- UV resistant
- Lengths from 250mm to 5000mm
- Silicone material (white or black)

Technical Information

Power (W/m)	24
Lumens (RGBW3000K)	R>100 - G>275 - B>75 - RGB>460 - 3000K>380
Material	Silicone
Bending	Vertical and Horizontal combined
CCT	RGBW • RGB
CRI	80
Control	DALI • DMX • Bluetooth Casambi
Beam Angle	20°x40°
LED	Nichia
Binning	3 Step MacAdam
Input Voltage (V)	24
Max length (1 Entry)	5mtr
Cutting	250mm
IP Rating	IP67
Operating Ambient Temp	-40°C to 55°C
Lifetime	>50,000hrs
Connection	500mm rear tail to bare end

Product Code

FX8-S - 1 - 2 - 3 - 4 - 5

Create your product code by choosing your specification from the product areas.

Final example codes are shown to the right.

Example Codes

FX8-S-RGBW-2040-B-67-XXXX

FX8-S-RGB-2040-W-67-XXXX

1 CCT

RGBW	RGBW
RGB	RGB

3 Body Finish

Black	B
White	W

5 Length

XXXXmm	XXXX
--------	------


2 Beam Angle

20°x40°	2040
---------	------

4 IP Rating

IP67	67
------	----

Specification Drawings



Adjustable bracket with 36mm and 50mm Aluminium profile

Ground spike adjustable bracket

Fixing Accessories

Flexus 8, adjustable bracket

Flexus 8, vertical bendable Aluminium profile 1000mm
Flexus 8, horizontal bendable Aluminium profile 1000mm


Flexus 8, straight Aluminium profile 2000mm
Flexus 8, straight Aluminium profile 1000mm
Flexus 8, straight Aluminium profile 500mm
Flexus 8, straight Aluminium profile 50mm

Flexus 8, straight Aluminium profile (including cable void) 2000mm
Flexus 8, straight Aluminium profile (including cable void) 1000mm
Flexus 8, straight Aluminium profile (including cable void) 500mm
Flexus 8, straight Aluminium profile (including cable void) 50mm



Assembly Caution

Min Bend Dia Vertically is **400mm**
Min Bend Dia Horizontally is **800mm**



Kemps Code

FX8-ADJ-BKT

FX8-BAP-36X41-1000-VB
FX8-BAP-36X41-1000-HB

FX8-SAP-36x41-2000
FX8-SAP-36x41-1000
FX8-SAP-36x41-500
FX8-SAP-36x41-50

FX8-SAP-50x41-2000
FX8-SAP-50x41-1000
FX8-SAP-50x41-500
FX8-SAP-50x41-2000

Complies with EN60598-1 and pertinent regulations

Specifications are subject to change without prior notice. Please refer to our website for most up to date version.



Contact our sales team for further assistance

0113 263 9039

sales@kempslighting.com

kempsarchitecturallighting.com